


Submittal Data



Polyisocyanurate foam half shells

Urecon's insulation manufacturing process and related ISO-9000 quality control procedures assure you of the highest quality product on the market today. This unique, time proven, void free process allows us to visually inspect the urethane foam insulation during manufacture. The jacket of choice shall be field applied to suit the application.

Application:

Urecon's polyisocyanurate foam half shells are suitable for existing piping systems that cannot be factory insulated. The applications would include but not be limited to:

- chilled water lines in warmer climates
- potable water or sewer lines to prevent freezing in colder regions.
- warm water or oil lines to 150°C (300°F)
- natural gas collector lines from the well head
- cryogenic lines

Core Pipe:

All types and sizes of pipe may be insulated with Urecon's polyurethane foam half shells. Please specify the type of pipe in order to size

the inside diameter of the half shells properly (e.g.: C.T.S. , I.P.S., D.I., or metric)

Insulation:

- Material, rigid polyisocyanurate foam
- Density: (ASTM D 1622) 27 to 32 kg/m³ (1.7 to 2 lbs/ft³).
- Compressive Strength: (ASTM D 1621) 131 to 158 kPa (19 to 23 lbs/in²).
- Closed Cell Content: 90% minimum.
- Water Absorption: 4% by volume.
- K factor: (ASTM C 518) 0,027 W/m⁰C (0.19 Btu. In/ft².hr.0F).
- Temperature limitations: in service, -45⁰ to 150⁰C (-49⁰ to 300⁰F)
- Supplied in 0,91m (3 ft) lengths

Fittings:

Two piece polyurethane foam insulation covers may be supplied for field installation to suit almost any fitting you may encounter. These fitting covers shall match the thickness of the insulation on the pipe.

**Polyisocyanurate foam half shells
submittal data sheet cont'd.**

Polyisocyanurate foam half shell submittal data sheet, con't...

Polyurethane foam half shells (based on I.P.S. diameter pipe)													
		25mm (1")				35mm (1 1/2")				50mm (2")			
Pipe Size		OD		Foam		OD		Foam		OD		Foam	
<i>In</i>	mm	<i>in</i>	mm	<i>in</i>	mm	<i>in</i>	Mm	<i>In</i>	mm	<i>in</i>	mm	<i>in</i>	mm
1/2"	12	3.00	76	1.1	28	3.67	93	1.4	36	5.25	133	2.2	56
3/4"	19	3.35	85	1.2	30	4.25	108	1.6	41	5.25	133	2.1	53
1"	25	3.75	95	1.2	30	4.50	114	1.7	43	5.25	133	2.1	53
1 1/4"	32	4.00	102	1.2	30	4.50	114	1.4	36	5.50	140	1.9	48
1 1/2"	38	4.25	108	1.2	30	5.00	127	1.6	41	6.13	156	2.1	53
2"	51	4.63	118	1.1	28	5.75	146	1.7	43	6.50	165	2.1	53
2 1/2"	64	5.13	130	1.1	28	6.13	156	1.6	41	6.75	171	1.9	48
3"	76	5.75	146	1.2	30	6.75	171	1.7	43	7.75	197	2.2	56
4"	102	6.75	171	1.1	28	7.75	197	1.6	41	8.75	222	2.2	56
5"	127	8.00	203	1.2	30	8.75	222	1.6	41	10.00	254	2.2	56
6"	152	9.00	229	1.2	30	10.00	254	1.7	43	11.00	279	2.2	56
8"	203	11.00	279	1.2	30	12.00	305	1.7	43	13.25	337	2.3	58
10"	254	13.75	349	1.5	38	14.00	356	1.6	41	15.50	394	2.4	61
12"	305	15.70	399	1.5	38	16.00	406	1.6	41	17.50	445	2.4	61
14"	356	x	x	x	x	17.75	450	1.9	48	18.80	478	2.4	61
16"	406	x	x	x	x	19.75	502	1.9	48	21.00	533	2.5	64
18"	457	x	x	x	x	x	x	x	x	23.00	584	2.5	64
20"	508	x	x	XX	x	x	x	x	x	25.00	635	2.5	64

*Highlighted areas indicate product submitted for this project.

CANADA

1800, av. Bédard
St-Lazare-de-Vaudreuil (Québec) J7T 2G4
Tél.: (450) 455-0961 Fax: (450) 455-0350
E-mail: sales.east@urecon.com

5010-43 Avenue
Calmar, Alberta T0C 0V0
Tel: (780) 985-3636 Fax: (780) 985-2466
E-mail: sales.west@urecon.com

WEB SITE: www.urecon.com

UNITED STATES

4185 South US1, Suite 102
Rockledge, FL 32955
Tel.: (321) 638-2364 Fax: (321) 638-2371
E-mail: sales.usa@urecon.com

ISO 9001:2000
Registered Company

Local Representative

